

GENERAL OVERVIEW

The following specification instruction is suitable for ALSYNITE EVERCOOL glass reinforced polyester sheeting. If further specification details are required, please contact the Alsynite Roofing Products Technical Department.

PRODUCT SPECIFICATION

- **Description:** The product shall be ALSYNITE EVERCOOL Glass Reinforced Polyester (GRP) Sheeting .
- **Profile:** The profile shall be.....
- **Class/Weight:** g/m²
- **Colour:** The colour shall be
- **Resin System:** Polyester general purpose orthophthalic resin with U.V. inhibitors.
- **Surface Coating:** **Top** - Melinex[®] A15, 20 micron nominal thickness, protection film.
Bottom - Laminated striped metalised film.
- **Cure Level:** In accordance with AS/NZS 4256:3:1994, the residual styrene level is less than 2% as measured by Gas Liquid Chromatograph.
- **Reinforcement:** Equi-disposed, Chopped Glass Rovings at minimum of 22%.
- **Quality:** Manufactured in accordance with Australian/New Zealand Standards AS/NZS 4256.3:1994.
- **Installation:** To be carried out in accordance with the Australian/New Zealand Design and Installation of sheet roof and wall cladding products AS/NZS 1562.3:1996 and Alsynite Roofing Products Pty Ltd Installation and Maintenance procedures.